

Level 3 DC Fast Chargers – 30 kW

Powerful and convenient Level 3 chargers

- Low-cost DC solution
- Full charge in just a few hours
- Wall mount for flexible site design



30 kW DC chargers

	LEDC-T30HV-480V-WSB-EWCRX	LEDC-T30HV-480V-WDD-EWCRX
Output power	30 kW (single port)	30 kW (dual port)
Mount	Wallbox	
Cable length	Single 16ft cable	Dual 16ft cables
Connectors	J1772 CCS-1 Combo	J1772 CCS-1 Combo & CHAdeMO

Input power	480V three-phase / 40A, 60A breaker
Max. output voltage	1000 VDC
Display	7" touch screen
Dimensions	21" x 12" x 27"
Weight	176 lbs (80kg)
Card reader	RFID
Network	Ethernet
WiFi	Yes
4G	Yes
Communication protocol	OCPP
Electrical protection	Over Voltage, Under Voltage, Over Current, Missing Ground. Output power disabled when output is short circuited
Enclosure rating	NEMA 3S, IK10
Regulatory compliance	UL-2202 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012 Canada: cUL 2202:2009, CSA C22.2#107.1:2016
Operating temperature	-30°C to 55°C (-22°F to 131°F)
Options	Credit card reader, cable retractor, 3G/4G modem
Warranty	2 years, parts only