

Level 3 DC Fast Chargers – 60kW

Powerful and convenient Level 3 DC Fast Chargers

- Simultaneous vehicle charging
- Market favorite
- Modular design for improved serviceability
- Ideal solution for most opportunity charging



60 kW DC chargers

	LEDC-T60LV-480V-PDD-EW-CRX	LEDC-T60LV-480V-PDC-EWCRX	LEDC-T60HV-480V-PDD-EW-CRX	LEDC-T60HV-480V-PDC-EW-CRX
Output power	60 kW (dual port)	60 kW (dual port)	60 kW (dual port)	60 kW (dual port)
Mount	Pedestal	Pedestal	Pedestal	Pedestal
Cable length	Dual 16ft cables	Dual 16ft cables	Dual 16ft cables	Dual 16ft cables
Connectors	J1772 CCS-1 Combo & CHAdeMO	2 x J1772 CCS-1 Combo	J1772 CCS-1 Combo & CHAdeMO	2 x J1772 CCS-1 Combo
Maximum output voltage	500V	500V	1000 V	1000V
Input Power	480V / 80A, 100A breaker, three phase			

Display	7" touch screen
Dimensions	29" x 19" x 72"
Weight	530 lbs (240kg)
Card reader	RFID
Network	Ethernet
Wifi	Yes
4G capable	Yes
Communication protocol	OCPP
Electrical protection	RCD 20 mA Type A. Over Voltage, Under Voltage, Over Current, Missing Ground
Enclosure rating	NEMA 3S, IK10
Regulatory compliance	UL-2202 EMC: EN 61000-6-1:2007, EN 61000-6-3:2007/A1:2011/AC:2012 Canada: cUL 2202:2009, CSA C22.2#107.1:2016
Operating temperature	-22°F to 131°F (-30°C to 55°C)
Options	Credit card reader, cable retractor, 3G/4G modem
Warranty	2 years, parts only